RNAV (GPS) RWY 27

WITTMAN RGNL (OSH)

WAAS	APP CRS		
CH **93534**	**274°**	Rwy Idg	**5648**
W27A		THRE	**778**
		Apt Elev	**808**

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C (-4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Fond Du Lac altimeter setting and increase all DA 31 feet and all MDA 40 feet; increase LPV and LNAV/VNAV all Cats visibility and LNAV Cats C and D visibility ⅛ mile, increase Circling Cat D ¼ mile. Baro-VNAV and VDP NA with Fond Du Lac altimeter setting. Circling to Rwys 5, 23, and 31 NA at night. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 3000 direct HETUP and hold.

ATIS	MILWAUKEE APP CON	OSHKOSH TOWER ★	GND CON	UNICOM
125.9	**127.0 263.075**	**118.5** (CTAF) Ⓛ **290.9**	**121.9**	**122.95**



EC-3, 26 JUN 2014 to 24 JUL 2014

EC-3, 26 JUN 2014 to 24 JUL 2014





CATEGORY	A	B	C	D
LPV DA	1028-¾	250 (300-¾)		
LNAV/VNAV DA	1070-1	292 (300-1)		
LNAV MDA	1140-1	362 (400-1)		
C CIRCLING	1280-1 472 (500-1)	1300-1 492 (500-1)	1360-1½ 552 (600-1½)	1440-2 632 (700-2)